



ITEM # RR-L750

## FLOOR FINISH

### HIGHLIGHTS

- Excellent gloss
- Superior response to high speed burnishing
- Excellent Durability

### TYPICAL PROPERTIES

- Specific Gravity: 1.02
- pH: 8.3
- Leveling: Excellent
- Film Formation: Excellent
- Gloss: Excellent
- Water resistance: Excellent
- Detergent resistance: Very Good - Excellent
- Removability: Excellent
- Black heal mark resistance: Very Good
- Slip Resistance: 0.6 (James Static Coefficient of Friction)
- Odor: Slight Ammonia
- Appearance: White Emulsion

## Finish Line

# FLOOR FINISH

## SUPERIOR RESPONSE TO HIGH SPEED BURNISHING

- Excellent Gloss
- Excellent Durability

This high solids, metal-crosslinked, modified acrylic floor finish provides excellent lay down gloss and superior response to high speed burnishing. It can be maintained with either conventional low-speed programs or infrequent (2-3 times a week) high speed burnishing.

### USE DIRECTIONS (New or existing floors)

- 1) Thoroughly strip floor with a stripper.
- 2) Rinse floor thoroughly with clean water.
- 3) Apply a sealer base (optional) to worn floors or high traffic floors to improve wear-resistance and enhance gloss.
- 4) Apply 2-4 coats of floor finish in uniform thin coats allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather.

### MAINTENANCE

- 1) Sweep as necessary.
- 2) Damp mop or scrub lightly with a mild, neutral detergent.
- 3) Spray buff or buff lightly with appropriate pad. Also excellent for high-speed buffing.
- 4) In high traffic areas, recoat worn spots as necessary.

### SAFETY CAUTIONS

Keep out of reach of children. It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Refer to M.S.D.S. for additional safety information.



DISTRIBUTED BY:  
ROADRUNNER INDUSTRIES, INC.  
ATLANTA, GEORGIA 30321

RR-L750/0805