



ITEM # RR-L775

ACRYLIC SEALER

Seal Good

ACRYLIC SEALER

**Ready To Use Floor Sealer
(for resilient flooring)**

- Excellent Gloss
- Excellent Durability
- Superior Response to High Speed Burnishing

A high solids all acrylic sealer for resilient flooring such as vinyl, linoleum and asphalt tiles. Compatible with most water based floor finishes. Removable with conventional floor finish strippers.

Directions: Strip floors thoroughly and prepare neutral dry floor. To seal, apply one thin coat of Seal Good and allow at least 30 minutes drying time. Then apply up to 4 coats of a floor polish of your choice, allowing at least 30 minutes drying time between coats. Daily maintenance requires sweeping and damp mopping or spray-buffing. Heavy traffic lanes or worn areas should be recoated periodically.

HIGHLIGHTS

- High solids
- Excellent adhesion
- Extends life of floor finishes

TYPICAL PROPERTIES

- Specific Gravity: 1.02
- Solids: 16%
- pH: 9.0
- Odor: Slight ammonia
- Appearance: White emulsion

SAFETY CAUTIONS

Keep out of reach of children. It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Refer to M.S.D.S. for additional safety information.



DISTRIBUTED BY:
ROADRUNNER INDUSTRIES, INC.
ATLANTA, GEORGIA 30321

RR-L75/0005